

## EARTHING EQUIPMENTS

### EARTH RODS

Ram Ratna offers to the customer a complete range of earthing equipments which are best suitable and most economically available

#### COPPER BONDED EARTH RODS – SECTIONAL

Ram Ratna earth rods are made from high tensile low carbon steel. Earth rods is made by molecularly bonding 99.9% pure electrolytic copper. To prevent oxidation of copper bonding, earth rods is treated with Benzol – Triazole derivatives. Threads on the rods are formed by roll threading process giving extra strength to the treads and eliminating risk of chipping of threads while driving the rod in the ground.



← Driving Stud

← Coupler

← Earth Rod

← Coupler

← Earth Rod

#### ROD DETAILS

Rod DIA. mm	Total Length	Thread Dia
12.5	1400	9/16"
12.5	1500	9/16"
12.5	1800	9/16"
12.5	2400	9/16"
14.2	1400	5/8"
14.2	1500	5/8"
14.2	1800	5/8"
14.2	2400	5/8"
16.0	1400	5/8"
16.0	1500	5/8"
16.0	1800	5/8"
16.0	2,400	5/8"
16.0	3,000	5/8"
17.2	1,400	3/4"
17.2	1,500	3/4"
17.2	1,800	3/4"
17.2	2,400	3/4"
17.2	3,000	3/4"

NOTE: UL LISTED RODS ARE MINIMUM 1/2" DIA. AND 2400mm IN LENGTH

#### THREADED COUPLERS

Made up of Copper Alloy for higher strength and countered bored to protect the rod threads from damage.

#### DRIVING BOLT

Made up of Re-usable high tensile steel Can be use many times over and suitable for power hammering.

#### Thread Dia

9/16"

5/8"

3/4"

#### Thread Dia

9/16"

5/8"

3/4"