Technical Data Sheet



FMP 501 Carbon Filament

Typical Applications: Valves, Boiler Feed Pumps

Service Media & conditions:

Used for High Speed, High Temperature & Pressure applications in sealing Boiler Feed Pumps, Super heated Steam, Chemically Inert to most media, not used for Acids & Oxidising Media.

Supply Data:

Size Range: 6 x 6 to 40 x 40 mm

Form: Square

Technical Data:

Material Number :	FMP 501
Type of Fibre :	Carbon filament Yarn
Carrier Fibre :	15/2
Type of Core :	Graphite
Metal Insertion/Jacketing	
Application Limit	-200°C to 600°C
Decomposition :	600°C
Operating Pressure (Max.) Rotating	35 Bar
Operating Pressure (Max.) Oscillating	100 Bar
Max Operating Pressure :	350 Bar
Temperature of Carrier Fibre:	
рН	0 - 14
Density (g/cm³)	1.0 -1.1

Physical Properties:

Size (mm)	6	8	10	12	16	18	20	25	30	40	
Weight (g/m)	36	64	100	144	256	324	400	625	900	1600	

Product versions:

With metal wire insertion-S.S.(FMP 501M) Impregnated with PTFE or Graphite — To reduce stem friction & corrosion inhibitor.

KITZ SEALS - Website: Kitz.com.vn - Email: info@kitz.com.vn

Chemical Resistance Chart

1	Water
2	Steam
3	Natural Solutions Dilute Acids
4	Dilute Acids
5	Mild Acids
6	Concentrated Acids
7	Dilute Alkalies
8	Strong Alkalies
9	Inert Gases
10	Acidic Vapours/ Gases
11	Solvents
12	Organic Compouds
13	Mineral Oil
14	Synthetic Oil
15	Abrasive Media
16	Bitumen
17 <	Lacqures

Legends: Suitable Conditional Suitable Not Suitable

All data quoted above are based on years of experience in production & operation of sealing elements, in view of the wide variety of possible installation & operating conditions one can not draw final conclusion in all application cases regarding the behaviour in gasket joint. The data may not therefore, be used to support any warranty claims.

Should you have any doubts about the choice of gasket material, please refer to us. Our engineering cell will be happy to assist you.

Ferolite Jointings Ltd
C-178, Site No.1 B.S. Road Industrial Area, Ghaziabad-201001 (U.P.) Website www.ferolite.com