Technical Data Sheet



FMP 524 Glass Fiber

Typical Applications: Filters, Boiler, Insulation

Service Media & conditions:

Used for Thermal insulation, Boiler pipe line, Furnaces & Ovens in Steel& Chemical Industry, Filters applications, Fuel Gas Valves, Kiln Covers, Acid & Alkali Valves Hot Expansion Joints.



Size Range: 6 x 6 to 60 x 60 mm

Form: Round/Sqare

Technical Data:



Physical Properties:

Size (mm)	6	8	10	12	16	18	20	25	30	40	50
Weight (g/m)	54	96	150	216	384	486	600	938	1350	2400	3750

Product versions:

Impregnated with Graphited PTFE emulsion also available.

Metal Wire Insertion of Chrome Steel (S.S.) wire (FMP 524 GM).

Metal Wire Insertion of Inconel wire (FMP 524 IN).

Chemical Resistance Chart

1	Water					
2	Steam					
3	Natural Solutions					
4	Dilute Acids					
5	Mild Acids					
6	Concentrated Acids					
7	Dilute Alkalies					
8	Strong Alkalies					
9	Inert Gases					
10	Acidic Vapours/ Gases					
11	Solvents					
12	Organic Compouds					
13	Mineral Oil					
14	Synthetic Oil					
15	Abrasive Media					
16	Bitumen					
17	Lacqures					

Legends : Suitable Conditional Suitable Not Suitable

All data quoted above are based on years of experience in production & operation of sealing elements, in view of the wide variety of possible installation & operating conditions one can not draw final conclusion in all application cases regarding the behaviour in gasket joint. The data may not therefore, be used to support any warranty claims.

Should you have any doubts about the choice of gasket material, please refer to us. Our engineering cell will be happy to assist you.

Ferolite Jointings Ltd

C-178, Site No.1 B.S. Road Industrial Area, Ghaziabad-201001 (U.P.)
Website www.ferolite.com