



VINDEC INDUSTRIAL EQUIPMENT JOINT STOCK COMPANY

Add: Lot A2, CN5 Str., Tu Liem Industrial Park, Bac Tu Liem Dist., Ha Noi City, Viet Nam

Tel: 024 6666 6667 - Website: <https://vindec.vn/> - Email: info@vindec.vn

Services & Solutions - ISO 9001: 2015

Pipe joints to BS EN 1514:2004							Table 7: PN25 Flanges		
Nominal size	Gasket inside diameter 2), 3)	IBC gasket outside diameter	Full face gasket				Type SR Gasket Outside Diameter	Type TG Gasket	
			Outside diameter	Holes		Bolt circle diameter		Inside Diameter	Outside Diameter
				No.	Diameter				
DN	mm	mm	mm		mm	mm	mm	mm	mm
10	Use PN40 Dimensions						Use PN40 Dimensions	Use PN40 Dimensions	
15									
20									
25									
32									
40									
50									
60 ¹⁾									
65									
80									
100									
125									
150									
200	220	284	360	12	26	310	Use PN40 Dimensions	Use PN40 Dimensions	
250	273	340	425	12	30	370			
300	324	400	485	16	30	430			
350	356	457	555	16	33	490			
400	407	514	620	16	36	550			
450	458	564	670	20	36	600			
500	508	624	730	20	36	660			
600	610	731	845	20	39	770			
700	712	833	960	24	42	875	777	751	777
800	813	942	1085	24	48	990	882	856	882
900	915	1042	1185	28	48	1090	987	961	987
1000	1016	1154	1320	28	56	1210	1092	1062	1092
1100	1120	1254	1420	32	56	1310			
1200	1220	1364	1530	32	56	1420			
1400	1420	1578	1755	36	62	1640			
1500 ¹⁾	1520	1688	1865	36	62	1750			
1600	1620	1798	1975	40	62	1860			
1800	1820	2000	2195	44	70	2070			
2000	2020	2230	2425	48	70	2300			
1) 2) 3) Relates to cast iron flanges only. Except tongue and groove gasket. See table 10 for inside diameters of gaskets to suit EN545, EN598 & EN969 flanges.									

All sizes stated are in good faith and have been checked, but final responsibility lies with the customer