

SBR Rubber Sheet

Styrene Butadiene Rubber Sheet

Thickness: 1-100mm

Length: 5m-30m

Width: 1-2m

Pattern: Smooth or textured

Specific Gravity: 1.3-1.8g/cm³

Color: Black, Blue, Grey, Red, Green, etc.

Typical Value Tensile: 3.0-10Mpa

Elongation: 200%-500%

Hardness: 45-70 Shore A

Working temperature: 85degree (185F)

Heat resistance after 72 hours: 100degree (212F)

Low working temperature: -25degree(-13F)



Density (G/cm ³)	Tensile Strength (Mpa)	Elongation (%)	Hardness (Shore A)	Thickness (mm)	Width (m)	Length (m)
1.35	5	350	60	1-100	0.5-2	1-50m
1.4	4	300	65			
1.5	3	260	65			
1.6	2.5	220	70			
1.7	2	180	70			



Density	Thickness(mm)	Width(m)	Length(m)	Weight(kgs)
1.5	3	1.2	10	54
	5	1.2	10	90
	10	1.2	5	90
1.6	3	1.2	10	57.6
	5	1.2	10	96
	10	1.2	5	96
1.7	3	1.2	10	61.2
	5	1.2	10	102
	10	1.2	5	102



SBR is commercial grade material, is ideal for abrasion resistant applications. This product makes a nice industrial surface rubber, protecting dropped parts from possible damage. It is a very cost effective alternative for applications which require a sturdy resilient industrial elastomer.