SBR Rubber Sheet

Good resistance to abrasion, high temperature, and aging. It is used for gaskets, flooring and etc. Suitable for current use where particular resistances to atmospheric agents, oils and heat are not required.

Thickness: 1mm to 100mm
Width: 1m to 2m
Standard width: 1m, 1.2m
Length: 1m to 50m
Standard length: 5m,10m, 20m

	Hardness Shore A	Density g/cm3	Tensile Strength Mpa	Elongation %	Temperature Range °C
SBR rubber sheet	70 +/-5	1.7	2	180%	-20 ~ 80
SBR rubber sheet	65 +/-5	1.6	2.5	200%	-20 ~ 80
SBR rubber sheet	65 +/-5	1.5	3	250%	-20 ~ 80
SBR rubber sheet	80 +/-5	1.5	3	200%	-20 ~ 80
SBR rubber sheet	60 +/-5	1.4	5	250%	-20 ~ 80
SBR rubber sheet	60 +/-5	1.35	6	250%	-20 ~ 80
SBR rubber sheet	50 +/-5	1.35	6	300%	-20 ~ 80

- All colors available.
- Cloth insertion, nylon insertion available.
- Cloth impression finish available.
- Custom specifications, shapes and sizes available.
- New product formula can be designed by request.