


Double Pitch Sprockets (for R Rollers): Steel, Stainless Steel

These are sprockets for Double Pitch chains.



Model Numbering Example

RF2050R -1B 1100T -SS

Size/Roller type _____
 No. of strands/Hub type _____
 No. of effective teeth: 1100T=11T

Series [Blank]: Steel
 Q : Hardened teeth
 SS : Stainless steel
 SST : Wear-resistant stainless steel

Standard Sprocket	Corrosion Resistant Sprocket	No. of Effective Teeth	Pitch Circle Dia. D_P	Outer Dia. D_O	Tooth Width T	Bore Dia. d		Hub		Approx. Mass (kg)
Steel	Stainless Steel					Pilot Bore	Max.	Dia. D_H	Length L	
Model No.	Model No.									
RF2040R-1B1000T	RF2040R-1B1000T-SS	10	82.20	93	7.3	12.7	32	52	25	0.5
RF2040R-1B1100T	RF2040R-1B1100T-SS	11	90.16	102	7.3	12.7	42	63	25	0.7
RF2040R-1B1200T	RF2040R-1B1200T-SS	12	98.14	110	7.3	12.7	42	63	25	0.8
RF2040R-1B1300T	RF2040R-1B1300T-SS	13	106.14	118	7.3	12.7	42	63	25	0.9
RF2040R-1B1400T	RF2040R-1B1400T-SS	14	114.15	127	7.3	12.7	42	63	25	0.9
RF2040R-1B1500T	RF2040R-1B1500T-SS	15	122.17	135	7.3	15.9	45	68	28	1.2
RF2040R-1B1600T	RF2040R-1B1600T-SS	16	130.20	143	7.3	15.9	45	68	28	1.2
RF2050R-1B1000T	RF2050R-1B1000T-SS	10	102.75	117	8.9	15.9	48	73	28	1.1
RF2050R-1B1100T	RF2050R-1B1100T-SS	11	112.70	127	8.9	15.9	48	73	28	1.2
RF2050R-1B1200T	RF2050R-1B1200T-SS	12	122.67	138	8.9	18	48	73	28	1.3
RF2050R-1B1300T	RF2050R-1B1300T-SS	13	132.67	148	8.9	18	48	73	28	1.4
RF2050R-1B1400T	RF2050R-1B1400T-SS	14	142.68	158	8.9	18	48	73	28	1.6
RF2050R-1B1500T	RF2050R-1B1500T-SS	15	152.71	168	8.9	18	48	73	28	1.7
RF2050R-1B1600T	RF2050R-1B1600T-SS	16	162.75	179	8.9	18	48	73	28	1.9
RF2060R-1B1000T	RF2060R-1B1000T-SS	10	123.29	140	11.9	18	55	83	45	2.3
RF2060R-1B1100T	RF2060R-1B1100T-SS	11	135.23	153	11.9	18	55	83	45	2.5
RF2060R-1B1200T	RF2060R-1B1200T-SS	12	147.21	165	11.9	18	55	83	45	2.8
RF2060R-1B1300T	RF2060R-1B1300T-SS	13	159.20	177	11.9	18	55	83	45	3.0
RF2060R-1B1400T	RF2060R-1B1400T-SS	14	171.22	190	11.9	18	55	83	45	3.3
RF2060R-1B1500T	RF2060R-1B1500T-SS	15	183.25	202	11.9	18	55	83	45	3.6
RF2060R-1B1600T	RF2060R-1B1600T-SS	16	195.29	214	11.9	18	55	83	45	3.9
RF2080R-1B1000T	RF2080R-1B1000T-SS	10	164.39	187	15	28	75	107	45	4.2
RF2080R-1B1100T	RF2080R-1B1100T-SS	11	180.31	203	15	28	75	107	45	4.7
RF2080R-1B1200T	RF2080R-1B1200T-SS	12	196.28	220	15	28	75	107	45	5.2
RF2080R-1B1300T	RF2080R-1B1300T-SS	13	212.27	237	15	28	75	107	45	5.8
RF2080R-1B1400T	RF2080R-1B1400T-SS	14	228.29	253	15	28	75	107	45	6.4
RF2080R-1B1500T	RF2080R-1B1500T-SS	15	244.33	269	15	28	75	107	45	7.1
RF2080R-1B1600T	RF2080R-1B1600T-SS	16	260.39	286	15	28	75	107	45	7.8
RF2100R-1B1100T		11	225.39	254	18	33	80	117	56	7.8
RF2120R-1B1100T		11	270.47	305	24	45	80	130	80	14.7
RF2160R-1B1100T		11	360.63	407	30	70	115	170	125	35.5

Note: 1. Models in shaded areas are made-to-order. All other models are stocked.

2. Material: Standard sprockets are machine structural carbon steel. Teeth are unhardened on all models.
 Corrosion resistant sprockets are stainless steel.