

Specification Chart

Output	Number of phases	Number of poles	Frequency Hz	Voltage V 50/60/60Hz	Rated current A 50/60/60Hz	Rated revolution r/min 50/60/60Hz	Protection	Cooling method	Rating	Insulation	Brake	
											Type	Rated torque (of motor torque)
0.75kW	Three-phase	4	50/60/60 (50/50/60/60)	200/200/220 (380/400/400/440)	4.0/3.5/3.4 (1.9/2.0/1.75/1.7)	1440/1730/1740 (1435/1440/1730/1740)	Totally enclosed (IP44)	Self-managed (JC411)	S1 (Continuous)	155 (F)	Non-excitation	At least 150%

Note 1: The values in parentheses under "Rated current" and "Rated revolution" are for 400 V class.

Note 2: The protective construction for the brake type is IP20.

Model number		Motor output kW	Frame number	Nominal reduction ratio	Number of reduction steps	Output shaft revolution		Allowable output shaft torque				Allowable output shaft O.H.L.		Drawing number of outline dimensions		
						r/min		N·m		{kgf·m}		N·m			{kgf·m}	
						50Hz	60Hz	50Hz		60Hz		N			{kgf}	
GMTR075	5	0.75	28	1/5	2	300	360	22.6	{ 2.31 }	18.8	{ 1.92}	1049	{ 107}	1		
	10			1/10		150	180	45.1	{ 4.6}	38.2	{ 3.9}	1666	{ 170}			
	15			1/15		100	120	67.6	{ 6.9}	56.8	{ 5.8}	2176	{ 222}			
	20			1/20		75	90	91.1	{ 9.3}	75.5	{ 7.7}	2636	{ 269}			
	25			1/25		60	72	114	{ 11.6}	94.1	{ 9.6}	3058	{ 312}			
	30		38	1/30	3	50	60	136	{ 13.9}	114	{ 11.6}	3459	{ 353}	2		
	40			1/40		37.5	45	175	{ 17.9}	146	{ 14.9}	4185	{ 427}			
	50			1/50		30	36	220	{ 22.4}	183	{ 18.7}	4861	{ 496}			
	60			1/60		25	30	264	{ 26.9}	220	{ 22.4}	5488	{ 560}			
	75			1/75		20	24	300	{ 30.6}	250	{ 25.5}	5792	{ 591}			
	100	42		1/100		3	15	18	439	{ 44.8}	369	{ 37.7}	7301		{ 745}	3
	120			1/120			12.5	15	527	{ 53.8}	439	{ 44.8}	8242		{ 841}	
	165			1/165			9.1	10.9	724	{ 73.9}	604	{ 61.6}	9800		{1000}	
	200			1/200			7.5	9	735	{ 75.0}	*613	*{ 62.5}	9800		{1000}	

Note 1: The nominal reduction ratio is shown as the reduction ratio.

Note 2: The output shaft revolution rate is calculated by dividing the motor synchronous revolution rate by the nominal reduction ratio.

For the actual reduction ratio, refer to page 36. Calculate the actual output revolution rate from the motor's rated revolution rate.

Note 3: The models marked with * are ones for which torque is limited.


Outline Dimensions

GMTR075-28U5 - 25 (B)

1

Reduction ratio : 5, 10, 15, 20, 25

Approx. weight : 19.0 (22.0) kg




GMTR075-38U30 - 75 (B)

2

Reduction ratio : 30, 40, 50, 60, 75

Approx. weight : 23.0 (26.0) kg




GMTR075-42F100 - 200 (B)

3

Reduction ratio : 100, 120, 165, 200

Approx. weight : 47.0 (50.0) kg



Note: The values in parentheses are for brake-equipped models.