


Model number

TK070R (1) + (2) L - (3) - (4)			
(1) Bending radius	(2) Number of links	(3) Fixed end	(4) Moving end
75		FOA	MOA
90		FIA	MIA
125		FOB	MOB
145		FIB	MIB

■ Steel bracket (including pin and circlip)

Model number	For cable carrier model number
TK070-MOA	TK070R ■■
TK070-MOB	
TK070-MIA	
TK070-MIB	
TK070-FOA	
TK070-FOB	
TK070-FIA	
TK070-FIB	

■ Bore dimensions



Example: Bore diameter (from left) 21/19/14/14
Distance between stay bores (from left) 20.5/24/20.5/18/17

Bore diameter	D_1	D_2	D_3	D_4	
	21	19	14	14	
Distance between stay bores	b_1	b_2	b_3	b_4	b_5
	20.5	24	20.5	18	17

Note: "From left" means as viewed from the direction of the A-A arrow view in the dimensional drawing.

■ Stay (thickness 10 mm)

Example:

TK070-SP45-100-10 B-TK

Stay height	Stay width	Stay thickness	Stay type
			B: Split type
			T: Unsplit type

Model number	Stay height A	Stay width B	For cable carrier model number
TK070-SP35-60-10T-TK	35	60	TK070R ■■
TK070-SP35-60-10B-TK			
TK070-SP35-80-10T-TK		80	
TK070-SP35-80-10B-TK			
TK070-SP35-100-10T-TK		100	
TK070-SP35-100-10B-TK			
TK070-SP35-125-10T-TK		125	
TK070-SP35-125-10B-TK			
TK070-SP35-150-10T-TK		150	
TK070-SP35-150-10B-TK			
TK070-SP35-200-10T-TK	45	200	TK070R ■■
TK070-SP35-200-10B-TK			
TK070-SP35-250-10T-TK		250	
TK070-SP35-250-10B-TK			
TK070-SP45-60-10T-TK		60	
TK070-SP45-60-10B-TK			
TK070-SP45-80-10T-TK		80	
TK070-SP45-80-10B-TK			
TK070-SP45-100-10T-TK		100	
TK070-SP45-100-10B-TK			
TK070-SP45-125-10T-TK		125	
TK070-SP45-125-10B-TK			
TK070-SP45-150-10T-TK		150	
TK070-SP45-150-10B-TK			
TK070-SP45-200-10T-TK		200	
TK070-SP45-200-10B-TK			
TK070-SP45-250-10T-TK		250	
TK070-SP45-250-10B-TK			
TK070-SP45-300-10T-TK		300	
TK070-SP45-300-10B-TK			
TK070-SP45-350-10T-TK		350	
TK070-SP45-350-10B-TK			

See page 20 for ordering information

See page 150 for product mass

TK / TKH

TKS

Steel Series

TKF

TKV

TKI