

Model number

TK180R (1) + (2) L - (3) - (4)

(1) Bending radius	(2) Number of links	(3) Fixed end	(4) Moving end
250		FOA	MOA
300		FIA	MIA
400		FOB	MOB
500		FIB	MIB
600			
700			

■ Stay

Example:


TK180-SP75-125-15 B-TK

Stay height	Stay width	Stay thickness	Stay type
			B: Split type
			T: Unsplit type

■ Stay (thickness 15 mm)

Model number	Stay height A	Stay width B	For cable carrier model number
TK180-SP75-125-15T-TK	75	125	TK180R ■■
TK180-SP75-125-15B-TK		125	
TK180-SP75-150-15T-TK		150	
TK180-SP75-150-15B-TK		150	
TK180-SP75-200-15T-TK		200	
TK180-SP75-200-15B-TK		200	
TK180-SP75-250-15T-TK		250	
TK180-SP75-250-15B-TK		250	
TK180-SP75-300-15T-TK		300	
TK180-SP75-300-15B-TK		300	
TK180-SP75-350-15T-TK	90	350	
TK180-SP75-350-15B-TK		350	
TK180-SP75-400-15T-TK		400	
TK180-SP75-400-15B-TK		400	
TK180-SP90-125-15T-TK		125	
TK180-SP90-125-15B-TK		125	
TK180-SP90-150-15T-TK		150	
TK180-SP90-150-15B-TK		150	
TK180-SP90-200-15T-TK		200	
TK180-SP90-200-15B-TK		200	
TK180-SP90-250-15T-TK		250	
TK180-SP90-250-15B-TK		250	
TK180-SP90-300-15T-TK		300	
TK180-SP90-300-15B-TK		300	
TK180-SP90-350-15T-TK		350	
TK180-SP90-350-15B-TK		350	
TK180-SP90-400-15T-TK		400	
TK180-SP90-400-15B-TK		400	

■ Bore dimensions



Example: Bore diameter (from left) 15/23/23/16
Distance between stay bores (from left) 25.5/23/27/23.5/26

Bore diameter	D_1	D_2	D_3	D_4	
	15	23	23	16	
Distance between stay bores	b_1	b_2	b_3	b_4	b_5
	25.5	23	27	23.5	26

Note: "From left" means as viewed from the direction of the A-A arrow view in the dimensional drawing.

■ Steel bracket (including pin and circlip)

Model number	For cable carrier model number
TK180-MOA	TK180R ■■
TK180-MOB	
TK180-MIA	
TK180-MIB	
TK180-FOA	
TK180-FOB	
TK180-FIA	
TK180-FIB	

■ Stay (thickness 20 mm)

Model number	Stay height A	Stay width B	For cable carrier model number
TK180-SP75-125-20T-TK	75	125	TK180R ■■
TK180-SP75-125-20B-TK		125	
TK180-SP75-150-20T-TK		150	
TK180-SP75-150-20B-TK		150	
TK180-SP75-200-20T-TK		200	
TK180-SP75-200-20B-TK		200	
TK180-SP75-250-20T-TK		250	
TK180-SP75-250-20B-TK		250	
TK180-SP75-300-20T-TK		300	
TK180-SP75-300-20B-TK		300	
TK180-SP75-350-20T-TK	90	350	
TK180-SP75-350-20B-TK		350	
TK180-SP75-400-20T-TK		400	
TK180-SP75-400-20B-TK		400	
TK180-SP75-450-20T-TK		450	
TK180-SP75-450-20B-TK		450	
TK180-SP75-500-20T-TK		500	
TK180-SP75-500-20B-TK		500	
TK180-SP90-125-20T-TK		125	
TK180-SP90-125-20B-TK		125	
TK180-SP90-150-20T-TK		150	
TK180-SP90-150-20B-TK		150	
TK180-SP90-200-20T-TK		200	
TK180-SP90-200-20B-TK		200	
TK180-SP90-250-20T-TK		250	
TK180-SP90-250-20B-TK		250	
TK180-SP90-300-20T-TK	110	300	
TK180-SP90-300-20B-TK		300	
TK180-SP90-350-20T-TK		350	
TK180-SP90-350-20B-TK		350	
TK180-SP90-400-20T-TK		400	
TK180-SP90-400-20B-TK		400	
TK180-SP90-450-20T-TK		450	
TK180-SP90-450-20B-TK		450	
TK180-SP90-500-20T-TK		500	
TK180-SP90-500-20B-TK		500	
TK180-SP90-550-20T-TK		550	
TK180-SP90-550-20B-TK		550	
TK180-SP90-600-20T-TK		600	
TK180-SP90-600-20B-TK		600	
TK180-SP110-125-20T-TK	110	125	
TK180-SP110-125-20B-TK		125	
TK180-SP110-150-20T-TK		150	
TK180-SP110-150-20B-TK		150	
TK180-SP110-200-20T-TK		200	
TK180-SP110-200-20B-TK		200	
TK180-SP110-250-20T-TK		250	
TK180-SP110-250-20B-TK		250	
TK180-SP110-300-20T-TK		300	
TK180-SP110-300-20B-TK		300	
TK180-SP110-350-20T-TK		350	
TK180-SP110-350-20B-TK		350	
TK180-SP110-400-20T-TK		400	
TK180-SP110-400-20B-TK		400	
TK180-SP110-450-20T-TK		450	
TK180-SP110-450-20B-TK		450	
TK180-SP110-500-20T-TK		500	
TK180-SP110-500-20B-TK		500	
TK180-SP110-550-20T-TK		550	
TK180-SP110-550-20B-TK		550	
TK180-SP110-600-20T-TK		600	
TK180-SP110-600-20B-TK		600	