
Universal Foot

Applications

The universal foot can be used as a foot for a conveyor or other equipment. Use it on an inclined floor or in a place where the level needs adjustment. The hole-drillable type can be fixed to the floor.

Installation Example


Use for leg parts of food machines.



Specification Table

■ Universal Foot






Tsubaki model no.		Allowable load		
	Bolt	Base plate	Antiskid rubber pad	kN {kgf}
TP-C17107T-UF	Stainless steel	Reinforced polyamide (color: black)	Oil proof rubber shore hardness 70 (color: black)	12.0 {1220}

Note: 1. Standard product.

^{2.} The allowable load is the maximum allowable load in a static state.





Tsubaki model no.	Diameter			Material			Allowable load	
	L	Lı	L ₂	М	Bolt	Base plate	Antiskid rubber pad	kN {kgf}
TP-C171054T-UF	94	97	60	M16	Stainless steel	Reinforced polyamide (color: black)	Oil proof rubber shore hardness 70 (color: black)	15.0{1530}
TP-C171056T-UF	179	182	145					
TP-C171060T-UF	1/9	102	145	M20				

Note: 1. Tsubaki model no. in boldface are standard products. Tsubaki model no. in normal face is a made-to-order product.

^{2.} The allowable load is the maximum allowable load in a static state.