OMRON

E3FA PHOTOELECTRIC SENSORS

A new generation in sensing performance



» Simplicity

» One family for all

» Non-stop detection

A new generation in sensing performance!

Producing more than a million per year, Omron is a world leader in photoelectric sensors. Backed by more than 40 years of experience, Omron is constantly enhancing its portfolio and has now completely redesigned and expanded its popular M18 cylindrical range. Renowned for its high quality and product reliability, Omron's new generation of photoelectric sensors represents one of the largest varieties of dependable and easy-to-use photoelectric sensors on the market. Regardless of your industry or application, the E3FA series has the right sensor for the job at the best price versus performance.

Simplicity

- Simple selection
- Simple installation

One family for all

- All standard applications covered
- A wide variety of models
- Models designed for special applications

Non-stop detection

- High quality and reliability
- High EMC protection
- High light immunity
- Robust and waterproof housing



Simplicity

Omron's compact E3FA series of photoelectric sensors is simple and quick to mount, as well as easy and intuitive to set-up. The large and robust adjuster makes life much easier for installers to adjust the sensor, as does the bright, high-power red LED, which is clearly visible for easy alignment, even over longer distances. Similarly, the sensor's LED status indicator can be viewed from long distances and wide angles.



Compact size and shape. Can be installed almost anywhere.



Visible LED light for easy alignment.



Bright LED indicators for the easy operational status checking.



Flush mounting option for smooth installation.

One family for all

Typically installed in industrial plants ranging from food and beverage, textiles, ceramics and brick production, through to logistics, there's always an E3FA model to fit your application. This extensive photoelectric sensor series with high reliability and enhanced performance includes through-beam, retro-reflective and diffuse reflective types in straight and radial versions. Straight versions are also available with background-suppression, limited-reflective detection, and transparent object detection types for special applications.
All models are available in plastic and metal housing.
UL certification (UL60947-5-2) and CSA certification (CSA-C22.2 No.60947-5-2) have been obtained.



E3FA Standard Series

Omron's well-known quality is built into this series, which exceeds market standards in terms of reliability and solves a wide range of applications in various industries.



Through-beam	20 m
Retro-reflective with MSR function	0.1 to 4 m with E39-R1S
Coaxial Retro-reflective with MSR function	0 to 500 mm with E39-R1S
Diffuse-reflective	100 mm 300 mm 1 m

E3RA Standard Series

E3RA provides a full line-up of radial types that increases mounting flexibility to match specific requirements.



Through-beam	15 m
Retro-reflective with MSR function	0.1 to 3 m with E39-R1S
Diffuse-reflective	100 mm 300 mm 700 mm

Application specific models



Limited-reflective types suitable for detecting transparant film to shiny, mirror film.



Transparent object detection types utilising Omron's unique technology for detecting objects with birefringent (double refraction) properties.



Background suppression types for the stable detection of different objects with various colours.

E3FA Special Models

The E3FA series includes special models to solve demanding applications, for example, in the food and packaging industry. This includes the detection of transparent or structured objects.



BGS (background suppression) 	100 mm
	200 mm
Limited distance reflective 	10 to 50 mm
Transparent detection with P-opaquing function 	100 to 500 mm with E39-RP1
Transparent detection with P-opaquing function 	0.1 to 2 m with E39-RP1

Non-stop detection

Especially designed for machines that never stop, the rugged E3FA series offers completely reliable sensing in a robust and waterproof housing that can withstand even high-pressure cleaning. Exceeding market standards, this series also has high EMC protection and light immunity. In addition, there is the added benefit of the high-power LED, which contributes to high sensing stability even in environments with dust or vibrations.



High power LED to compensate for dirt and misalignment.



Pulse synchronisation for high ambient light immunity.



Intensive shielding for high electromagnetic noise immunity.



Tight housing construction for high-level water protection.

Ordering Information



Sensors (E3FA Plastic housing) [Refer to *Dimensions on page 21.*]

Red light Infrared light

Sensor type	Sensing distance	Connection method	Model	
			NPN output	PNP output
Through-beam *1. 	20 m	pre-wired	**set E3FA-TN11 2M** Emitter E3FA-TN11-L 2M Receiver E3FA-TN11-D 2M	**set E3FA-TP11 2M** Emitter E3FA-TP11-L 2M Receiver E3FA-TP11-D 2M
		M12 connector	**set E3FA-TN21** Emitter E3FA-TN21-L Receiver E3FA-TN21-D	**set E3FA-TP21** Emitter E3FA-TP21-L Receiver E3FA-TP21-D
	15 m	pre-wired	**set E3FA-TN12 2M** Emitter E3FA-TN12-L 2M Receiver E3FA-TN12-D 2M	**set E3FA-TP12 2M** Emitter E3FA-TP12-L 2M Receiver E3FA-TP12-D 2M
		M12 connector	**set E3FA-TN22** Emitter E3FA-TN22-L Receiver E3FA-TN22-D	**set E3FA-TP22** Emitter E3FA-TP22-L Receiver E3FA-TP22-D
Retro-reflective with MSR function *2. 	0.1 to 4 m with E39-R1S	pre-wired	**E3FA-RN11 2M**	**E3FA-RP11 2M**
		M12 connector	**E3FA-RN21**	**E3FA-RP21**
Coaxial Retro-reflective with MSR function *2. 	0 to 500 mm with E39-R1S	pre-wired	**E3FA-RN12 2M**	**E3FA-RP12 2M**
		M12 connector	**E3FA-RN22**	**E3FA-RP22**
Diffuse-reflective 	100 mm	pre-wired	**E3FA-DN11 2M**	**E3FA-DP11 2M**
		M12 connector	**E3FA-DN21**	**E3FA-DP21**
	300 mm	pre-wired	**E3FA-DN12 2M**	**E3FA-DP12 2M**
		M12 connector	**E3FA-DN22**	**E3FA-DP22**
	1 m	pre-wired	**E3FA-DN13 2M**	**E3FA-DP13 2M**
		M12 connector	**E3FA-DN23**	**E3FA-DP23**
	100 mm	pre-wired	**E3FA-DN14 2M**	**E3FA-DP14 2M**
		M12 connector	**E3FA-DN24**	**E3FA-DP24**
	300 mm	pre-wired	**E3FA-DN15 2M**	**E3FA-DP15 2M**
		M12 connector	**E3FA-DN25**	**E3FA-DP25**
	1 m	pre-wired	**E3FA-DN16 2M**	**E3FA-DP16 2M**
		M12 connector	**E3FA-DN26**	**E3FA-DP26**
BGS (background suppression) 	100 mm	pre-wired	**E3FA-LN11 2M**	**E3FA-LP11 2M**
		M12 connector	**E3FA-LN21**	**E3FA-LP21**
	200 mm	pre-wired	**E3FA-LN12 2M**	**E3FA-LP12 2M**
		M12 connector	**E3FA-LN22**	**E3FA-LP22**
Limited distance reflective 	10 to 50 mm	pre-wired	**E3FA-VN11 2M**	**E3FA-VP11 2M**
		M12 connector	**E3FA-VN21**	**E3FA-VP21**
Transparent detected with P-opaquing function *2. 	100 to 500 mm with E39-RP1	pre-wired	**E3FA-BN11 2M**	**E3FA-BP11 2M**
		M12 connector	**E3FA-BN21**	**E3FA-BP21**
Transparent detected with P-opaquing function *2. 	0.1 to 2 m with E39-RP1	pre-wired	**E3FA-BN12 2M**	**E3FA-BP12 2M**
		M12 connector	**E3FA-BN22**	**E3FA-BP22**

*1. The set type includes the emitter and receiver.
*2. The Reflector is sold separately. Select the Reflector model most suited to the application.



Sensors (E3RA Plastic housing) [Refer to *Dimensions on page 21.*]

Red light

Sensor type	Sensing distance	Connection method	Model	
			NPN output	PNP output
Through-beam *1. 	15 m	pre-wired	**set E3RA-TN11 2M** Emitter E3RA-TN11-L 2M Receiver E3RA-TN11-D 2M	**set E3RA-TP11 2M** Emitter E3RA-TP11-L 2M Receiver E3RA-TP11-D 2M
		M12 connector	**set E3RA-TN21** Emitter E3RA-TN21-L Receiver E3RA-TN21-D	**set E3RA-TP21** Emitter E3RA-TP21-L Receiver E3RA-TP21-D
Retro-reflective with MSR function *2. 	0.1 to 3 m with E39-R1S	pre-wired	**E3RA-RN11 2M**	**E3RA-RP11 2M**
		M12 connector	**E3RA-RN21**	**E3RA-RP21**
Diffuse-reflective 	100 mm	pre-wired	**E3RA-DN11 2M**	**E3RA-DP11 2M**
		M12 connector	**E3RA-DN21**	**E3RA-DP21**
	300 mm	pre-wired	**E3RA-DN12 2M**	**E3RA-DP12 2M**
		M12 connector	**E3RA-DN22**	**E3RA-DP22**
	700 mm	pre-wired	**E3RA-DN13 2M**	**E3RA-DP13 2M**
		M12 connector	**E3RA-DN23**	**E3RA-DP23**

*1. The set type includes the emitter and receiver.
*2. The Reflector is sold separately. Select the Reflector model most suited to the application.



Sensors (E3FB/E3RB Metal housing) [Refer to *Dimensions on page 22.*]

Red light

Sensor type	Sensing distance	Connection method	Model	
			NPN output	PNP output
Through-beam *1.	20 m	pre-wired	**set E3FB-TN11 2M** Emitter E3FB-TN11-L 2M Receiver E3FB-TN11-D 2M	**set E3FB-TP11 2M** Emitter E3FB-TP11-L 2M Receiver E3FB-TP11-D 2M
		M12 connector	**set E3FB-TN21** Emitter E3FB-TN21-L Receiver E3FB-TN21-D	**set E3FB-TP21** Emitter E3FB-TP21-L Receiver E3FB-TP21-D
Retro-reflective with MSR function *2.	0.1 to 4 m with E39-R1S	pre-wired	**E3FB-RN11 2M**	**E3FB-RP11 2M**
		M12 connector	**E3FB-RN21**	**E3FB-RP21**
Coaxial Retro-reflective with MSR function *2.	0 to 500 mm with E39-R1S	pre-wired	**E3FB-RN12 2M**	**E3FB-RP12 2M**
		M12 connector	**E3FB-RN22**	**E3FB-RP22**
Diffuse-reflective	100 mm	pre-wired	**E3FB-DN11 2M**	**E3FB-DP11 2M**
		M12 connector	**E3FB-DN21**	**E3FB-DP21**
	300 mm	pre-wired	**E3FB-DN12 2M**	**E3FB-DP12 2M**
		M12 connector	**E3FB-DN22**	**E3FB-DP22**
	1 m	pre-wired	**E3FB-DN13 2M**	**E3FB-DP13 2M**
		M12 connector	**E3FB-DN23**	**E3FB-DP23**
BGS (background suppression)	100 mm	pre-wired	**E3FB-LN11 2M**	**E3FB-LP11 2M**
		M12 connector	**E3FB-LN21**	**E3FB-LP21**
	200 mm	pre-wired	**E3FB-LN12 2M**	**E3FB-LP12 2M**
		M12 connector	**E3FB-LN22**	**E3FB-LP22**
Limited distance reflective	10 to 50 mm	pre-wired	**E3FB-VN11 2M**	**E3FB-VP11 2M**
		M12 connector	**E3FB-VN21**	**E3FB-VP21**
Transparent detected with P-opaquing function *2.	100 to 500 mm with E39-RP1	pre-wired	**E3FB-BN11 2M**	**E3FB-BP11 2M**
		M12 connector	**E3FB-BN21**	**E3FB-BP21**
Transparent detected with P-opaquing function *2.	0.1 to 2 m with E39-RP1	pre-wired	**E3FB-BN12 2M**	**E3FB-BP12 2M**
		M12 connector	**E3FB-BN22**	**E3FB-BP22**
Through-beam *1.	15 m	pre-wired	**set E3RB-TN11 2M** Emitter E3RB-TN11-L 2M Receiver E3RB-TN11-D 2M	**set E3RB-TP11 2M** Emitter E3RB-TP11-L 2M Receiver E3RB-TP11-D 2M
		M12 connector	**set E3RB-TN21** Emitter E3RB-TN21-L Receiver E3RB-TN21-D	**set E3RB-TP21** Emitter E3RB-TP21-L Receiver E3RB-TP21-D
Retro-reflective with MSR function *2.	0.1 to 3 m with E39-R1S	pre-wired	**E3RB-RN11 2M**	**E3RB-RP11 2M**
		M12 connector	**E3RB-RN21**	**E3RB-RP21**
Diffuse-reflective	100 mm	pre-wired	**E3RB-DN11 2M**	**E3RB-DP11 2M**
		M12 connector	**E3RB-DN21**	**E3RB-DP21**
	300 mm	pre-wired	**E3RB-DN12 2M**	**E3RB-DP12 2M**
		M12 connector	**E3RB-DN22**	**E3RB-DP22**
	700 mm	pre-wired	**E3RB-DN13 2M**	**E3RB-DP13 2M**
		M12 connector	**E3RB-DN23**	**E3RB-DP23**

*1. The set type includes the emitter and receiver.
*2. The Reflector is sold separately. Select the Reflector model most suited to the application.

Reflectors [Refer to *Dimensions on page 23.*]

Reflectors required for Retro-reflective Sensors: A Reflector is not provided with the Sensor. Be sure to order a Reflector separately.

Sensor	Sensing distance	Appearance	Model	Quantity	Remarks
E3FA-R□1 E3FB-R□1	0.1 to 4 m		**E39-R1S**	1	for E3FA-R□, E3RA-R□, E3FB-R□ and E3RB-R□
E3FA-R□2 E3FB-R□2	0 to 500 mm				
E3FA-B□1 E3FB-B□1	100 to 500 mm		**E39-RP1**	1	for E3FA-B□ and E3FB-B□
E3FA-B□2 E3FB-B□2	0.1 to 2 m				

Mounting brackets [Refer to *Dimensions on page 23.*]

A Mounting Bracket is not enclosed with the Sensor. Order a Mounting Bracket separately if required.

Sensor	Appearance	Model (Material)	Quantity	Remarks
all types		**E39-L183** (SUS304)	1	Mounting bracket
E3FA-□ E3RA-□		**E39-L182** (POM)	1	Flush mounting bracket

Sensor I/O connectors

Models for Connectors: A Connector is not provided with the Sensor. Be sure to order a Connector separately.

Sensor	Size	Cable	Appearance	Cable type		Model
M12 connector types	M12	Standard	Straight 	2 m	4-wire	**XS2F-M12PVC4S2M**
				5 m		**XS2F-M12PVC4S5M**
			Angle 	2 m		**XS2F-M12PVC4A2M**
				5 m		**XS2F-M12PVC4A5M**

Model Number Legend

E3□-□□□□-(□)□

1 2 3 4 5 6 7

1. Series name
FA: Cylindrical, Straight type, Plastic housing
RA: Cylindrical, Radial type, Plastic housing
FB: Cylindrical, Straight type, Metal housing
RB: Cylindrical, Radial type, Metal housing

2. Sensing method
T: Through-beam
R: Retro-reflective with MSR function
D: Diffuse-reflective
L: Background suppression
V: Limited distance reflective
B: Transparent detected with P-opaquing function

3. Output
P: PNP
N: NPN

4. Connection
1: Cable
2: Connector, M12, 4-pin

5. Difference of sensing distance, difference of light source
Sequential number

6. Emitter/Receiver
D: Receiver
L: Emitter

7. Cable length
Blank: Connector type

e.g., E3FA-TP11 2M;
Cylindrical, Straight type, Plastic housing/ Through-beam/ PNP/ Cable/ Difference of Sensing distance/ Cable length of 2M
E3RA-TN21-D;
Cylindrical, Radial type, Plastic housing/ Through-beam/ NPN/ Connector, M12, 4-pin/ Difference of Sensing distance/ Receiver/ Connector type
E3FA-VP21;
Cylindrical, Straight type, Plastic housing/ Limited distance reflective/ PNP/ Connector, M12, 4-pin/ Difference of Sensing distance/ Connector type

Ratings and Specifications

Straight type (E3FA/E3FB)

Item	Sensing method		Through-beam		Retro-reflective with MSR function	Coaxial Retro-reflective with MSR function
Model	NPN output	Pre-wired	E3F□-TN11 2M	E3FA-TN12 2M	E3F□-RN11 2M	E3F□-RN12 2M
		M12 Connector	E3F□-TN21	E3FA-TN22	E3F□-RN21	E3F□-RN22
	PNP output	Pre-wired	E3F□-TP11 2M	E3FA-TP12 2M	E3F□-RP11 2M	E3F□-RP12 2M
		M12 Connector	E3F□-TP21	E3FA-TP22	E3F□-RP21	E3F□-RP22
Sensing distance			20 m	15 m	0.1 to 4 m (with E39-R1S)	0 to 500 mm (with E39-R1S)
Spot diameter (reference value)			—			
Standard sensing object			Opaque: 7 mm dia.min.		Opaque: 75 mm dia.min.	
Differential travel			—			
Directional angle			2° min.			
Light source (wavelength)			Red LED (624 nm)	Infrared LED (850 nm)	Red LED (624 nm)	
Power supply voltage *1			10 to 30 VDC (include voltage ripple of 10%(p-p) max.)			
Current consumption			40 mA max. (Emitter 25 mA max. Receiver 15 mA max.)		25 mA max.	
Control output			NPN/PNP (open collector) Load current: 100 mA max. (Residual voltage: 3 V max.), Load power supply voltage: 30 VDC max. *2			
Operation mode			Light-ON/Dark-ON selectable by wiring			
Indicator			Operation indicator (orange) Stability indicator (green) Power indicator (green): only Emitter of Through-beam			
Protection circuits			Power supply reverse polarity protection, Output short-circuit protection, and Output reverse polarity protection			
Response time			0.5 ms			
Sensitivity adjustment			One-turn adjuster			
Ambient illumination (Receiver side)			Incandescent lamp: 3,000 lx max./ Sunlight: 10,000 lx max.			
Ambient temperature range *3			Pre-wired Models Operating: -25 to 55°C/ Storage: -40 to 70°C (with no icing or condensation) M12 Connector Models Operating: -40 to 55°C/ Storage: -40 to 70°C (with no icing or condensation)			
Ambient humidity range			Operating: 35 to 85%/ Storage: 35 to 95% (with no condensation)			
Insulation resistance			20 MΩ min. at 500 VDC			
Dielectric strength			1,000 VAC at 50/60 Hz for 1 min. between current-carrying parts and case			
Vibration resistance			Destruction: 10 to 55 Hz, 1.5 mm double amplitude for 2 hours each in X, Y and Z directions			
Shock resistance			Destruction: 500 m/s² 3 times each in X, Y and Z directions			
Degree of protection			IEC: IP67, DIN 40050-9: IP69K *4			
Weight (packed state/only sensor)	Pre-wired cable (2M)		**E3FA:** Approx. 110 g/ Approx. 50 g, respectively, **E3FB:** Approx. 175 g/ Approx. 65 g, respectively		**E3FA:** Approx. 60 g/ Approx. 50 g, **E3FB:** Approx. 95 g/ Approx. 65 g	
	Connector		**E3FA:** Approx. 30 g/ Approx. 10 g, respectively, **E3FB:** Approx. 85 g/ Approx. 20 g, respectively		**E3FA:** Approx. 20 g/ Approx. 10 g, **E3FB:** Approx. 50 g/ Approx. 20 g	
Material	Case		**E3FA:** ABS, **E3FB:** Nickel-brass			
	Lens and Display		PMMA			
	Adjuster		POM			
	Nut		**E3FA:** POM, **E3FB:** Nickel-brass			
Accessories			Instruction sheet M18 nuts (4 pcs)		Instruction sheet M18 nuts (2 pcs)	

Note: 1. Altitude: Up to 2,000 m, Pollution degree: 3, Enclosure type: Type1.
*1. UL power supply voltage rating is 10 to 26.4 VDC.
*2. UL load power supply voltage rating is 26.4 VDC max.
*3. UL temperature rating is 40°C maximum in operation.
*4. IP69K Degree of Protection Specifications
IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.
The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.
The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



Straight type (E3FA/E3FB)

Item	Sensing method		Diffuse-reflective					
Model	NPN output	Pre-wired	E3F□-DN11 2M	E3F□-DN12 2M	E3F□-DN13 2M	E3FA-DN14 2M	E3FA-DN15 2M	E3FA-DN16 2M
		M12 Connector	E3F□-DN21	E3F□-DN22	E3F□-DN23	E3FA-DN24	E3FA-DN25	E3FA-DN26
	PNP output	Pre-wired	E3F□-DP11 2M	E3F□-DP12 2M	E3F□-DP13 2M	E3FA-DP14 2M	E3FA-DP15 2M	E3FA-DP16 2M
		M12 Connector	E3F□-DP21	E3F□-DP22	E3F□-DP23	E3FA-DP24	E3FA-DP25	E3FA-DP26
Sensing distance			100 mm (white paper: 300 × 300 mm)	300 mm (white paper: 300 × 300 mm)	1 m (white paper: 300 × 300 mm)	100 mm (white paper: 300 × 300 mm)	300 mm (white paper: 300 × 300 mm)	1 m (white paper: 300 × 300 mm)
Spot diameter (reference value)			40 × 45 mm Sensing distance of 100 mm	40 × 50 mm Sensing distance of 300 mm	120 × 150 mm Sensing distance of 1 m	40 × 45 mm Sensing distance of 100 mm	40 × 50 mm Sensing distance of 300 mm	120 × 150 mm Sensing distance of 1 m
Standard sensing object			—					
Differential travel			20% max.					
Directional angle			—					
Light source (wavelength)			Red LED (624 nm)			Infrared LED (850 nm)		
Power supply voltage *1			10 to 30 VDC (include voltage ripple of 10%(p-p) max.)					
Current consumption			25 mA max.					
Control output			NPN/PNP (open collector) Load current: 100 mA max. (Residual voltage: 3 V max.), Load power supply voltage: 30 VDC max. *2					
Operation mode			Light-ON/Dark-ON selectable by wiring					
Indicator			Operation indicator (orange) Stability indicator (green)					
Protection circuits			Power supply reverse polarity protection, Output short-circuit protection, and Output reverse polarity protection					
Response time			0.5 ms					
Sensitivity adjustment			One-turn adjuster					
Ambient illumination (Receiver side)			Incandescent lamp: 3,000 lx max./ Sunlight: 10,000 lx max.					
Ambient temperature range *3			Pre-wired Models Operating: -25 to 55°C/ Storage: -40 to 70°C (with no icing or condensation) M12 Connector Models Operating: -40 to 55°C/ Storage: -40 to 70°C (with no icing or condensation)					
Ambient humidity range			Operating: 35 to 85%/ Storage: 35 to 95% (with no condensation)					
Insulation resistance			20 MΩ min. at 500 VDC					
Dielectric strength			1,000 VAC at 50/60 Hz for 1 min. between current-carrying parts and case					
Vibration resistance			Destruction: 10 to 55 Hz, 1.5 mm double amplitude for 2 hours each in X, Y and Z directions					
Shock resistance			Destruction: 500 m/s^2 3 times each in X, Y and Z directions					
Degree of protection			IEC: IP67, DIN 40050-9: IP69K *4					
Weight (packed state/only sensor)	Pre-wired cable (2M)		**E3FA:** Approx. 60 g/ Approx. 50 g, **E3FB:** Approx. 95 g/ Approx. 65 g					
	Connector		**E3FA:** Approx. 20 g/ Approx. 10 g, **E3FB:** Approx. 50 g/ Approx. 20 g					
Material	Case		**E3FA:** ABS, **E3FB:** Nickel-brass					
	Lens and Display		PMMA					
	Adjuster		POM					
	Nut		**E3FA:** POM, **E3FB:** Nickel-brass					
Accessories			Instruction sheet M18 nuts (2 pcs)					

Note: 1. Altitude: Up to 2,000 m, Pollution degree: 3, Enclosure type: Type1.
*1. UL power supply voltage rating is 10 to 26.4 VDC.
*2. UL load power supply voltage rating is 26.4 VDC max.
*3. UL temperature rating is 40°C maximum in operation.
*4. IP69K Degree of Protection Specifications
IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.
The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.
The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



Straight type (E3FA/E3FB)

Model / Item	Sensing method		BGS (Background suppression)		Limited distance reflective	Transparent detected with P-opaquing function	
	NPN output	Pre-wired	E3F□-LN11 2M	E3F□-LN12 2M	E3F□-VN11 2M	E3F□-BN11 2M	E3F□-BN12 2M
		M12 Connector	E3F□-LN21	E3F□-LN22	E3F□-VN21	E3F□-BN21	E3F□-BN22
	PNP output	Pre-wired	E3F□-LP11 2M	E3F□-LP12 2M	E3F□-VP11 2M	E3F□-BP11 2M	E3F□-BP12 2M
		M12 Connector	E3F□-LP21	E3F□-LP22	E3F□-VP21	E3F□-BP21	E3F□-BP22
Sensing distance			100 mm (white paper: 300 × 300 mm)	200 mm (white paper: 300 × 300 mm)	10 to 50 mm (glass(t = 1.0 mm): 150 × 150 mm)	100 to 500 mm (with E39-RP1)	0.1 to 2 m (with E39-RP1)
Spot diameter (reference value)			10 × 10 mm Sensing distance of 100 mm	10 × 15 mm Sensing distance of 200 mm	10 × 10 mm Sensing distance of 50 mm	—	
Standard sensing object			—			glass(t = 1.0 mm): 150 × 150 mm	
Differential travel			20% max.		—		
Directional angle			—				
Light source (wavelength)			Red LED (624 nm)				
Power supply voltage *1			10 to 30 VDC (include voltage ripple of 10%(p-p) max.)				
Current consumption			25 mA max.				
Control output			NPN/PNP (open collector) Load current: 100 mA max. (Residual voltage: 3 V max.), Load power supply voltage: 30 VDC max. *2				
Operation mode			Light-ON/Dark-ON selectable by wiring				
Indicator			Operation indicator (orange) Stability indicator (green)				
Protection circuits			Power supply reverse polarity protection, Output short-circuit protection, and Output reverse polarity protection				
Response time			0.5 ms				
Sensitivity adjustment			Fixed		One-turn adjuster		
Ambient illumination (Receiver side)			Incandescent lamp: 3,000 lx max./ Sunlight: 10,000 lx max.				
Ambient temperature range *3			Pre-wired Models Operating: -25 to 55°C/ Storage: -40 to 70°C (with no icing or condensation) M12 Connector Models Operating: -40 to 55°C/ Storage: -40 to 70°C (with no icing or condensation)				
Ambient humidity range			Operating: 35 to 85%/ Storage: 35 to 95% (with no condensation)				
Insulation resistance			20 MΩ min. at 500 VDC				
Dielectric strength			1,000 VAC at 50/60 Hz for 1 min. between current-carrying parts and case				
Vibration resistance			Destruction: 10 to 55 Hz, 1.5 mm double amplitude for 2 hours each in X, Y and Z directions				
Shock resistance			Destruction: 500 m/s^2 3 times each in X, Y and Z directions				
Degree of protection			IEC: IP67, DIN 40050-9: IP69K *4				
Weight (packed state/only sensor)	Pre-wired cable (2M)		**E3FA:** Approx. 60 g/ Approx. 50 g, **E3FB:** Approx. 95 g/ Approx. 65 g				
	Connector		**E3FA:** Approx. 20 g/ Approx. 10 g, **E3FB:** Approx. 50 g/ Approx. 20 g				
Material	Case		**E3FA:** ABS, **E3FB:** Nickel-brass				
	Lens and Display		PMMA				
	Adjuster		POM				
	Nut		**E3FA:** POM, **E3FB:** Nickel-brass				
Accessories			Instruction sheet M18 nuts (2 pcs)				

Note: 1. Altitude: Up to 2,000 m, Pollution degree: 3, Enclosure type: Type1.
*1. UL power supply voltage rating is 10 to 26.4 VDC.
*2. UL load power supply voltage rating is 26.4 VDC max.
*3. UL temperature rating is 40°C maximum in operation.
*4. IP69K Degree of Protection Specifications
IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.
The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.
The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



Radial type (E3RA/E3RB)

Item	Sensing method		Through-beam	Retro-reflective with MSR function	Diffuse-reflective		
Model	NPN output	Pre-wired	E3R□-TN11 2M	E3R□-RN11 2M	E3R□-DN11 2M	E3R□-DN12 2M	E3R□-DN13 2M
		M12 Connector	E3R□-TN21	E3R□-RN21	E3R□-DN21	E3R□-DN22	E3R□-DN23
	PNP output	Pre-wired	E3R□-TP11 2M	E3R□-RP11 2M	E3R□-DP11 2M	E3R□-DP12 2M	E3R□-DP13 2M
		M12 Connector	E3R□-TP21	E3R□-RP21	E3R□-DP21	E3R□-DP22	E3R□-DP23
Sensing distance			15 m	0.1 to 3 m (with E39-R1S)	100 mm (white paper: 300 × 300 mm)	300 mm (white paper: 300 × 300 mm)	700 mm (white paper: 300 × 300 mm)
Spot diameter (reference value)			—		35 × 40 mm Sensing distance of 100 mm	40 × 45 mm Sensing distance of 300 mm	90 × 120 mm Sensing distance of 700 mm
Standard sensing object			Opaque: 7 mm dia.min.	Opaque: 75 mm dia.min.	—		
Differential travel			—		20% max.		
Directional angle			2° min.		—		
Light source (wavelength)			Red LED (624 nm)				
Power supply voltage *1			10 to 30 VDC (include voltage ripple of 10%(p-p) max.)				
Current consumption			40mA max. (Emitter 25 mA max. Receiver 15 mA max.)	25 mA max.			
Control output			NPN/PNP (open collector) Load current: 100 mA max. (Residual voltage: 2 V max.), Load power supply voltage: 30 VDC max. *2				
Operation mode			Light-ON/Dark-ON selectable by wiring				
Indicator			Operation indicator (orange) Stability indicator (green) Power indicator (green): only Emitter of Through-beam				
Protection circuits			Power supply reverse polarity protection, Output short-circuit protection, and Output reverse polarity protection				
Response time			0.5 ms				
Sensitivity adjustment			One-turn adjuster				
Ambient illumination (Receiver side)			Incandescent lamp: 3,000 lx max./ Sunlight: 10,000 lx max.				
Ambient temperature range *3			Pre-wired Models Operating: -25 to 55°C/ Storage: -40 to 70°C (with no icing or condensation) M12 Connector Models Operating: -40 to 55°C/ Storage: -40 to 70°C (with no icing or condensation)				
Ambient humidity range			Operating: 35 to 85%/ Storage: 35 to 95% (with no condensation)				
Insulation resistance			20 MΩ min. at 500 VDC				
Dielectric strength			1,000 VAC at 50/60 Hz for 1 min. between current-carrying parts and case				
Vibration resistance			Destruction: 10 to 55 Hz, 1.5 mm double amplitude for 2 hours each in X, Y and Z directions				
Shock resistance			Destruction: 500 m/s^2 3 times each in X, Y and Z directions				
Degree of protection			IEC: IP67, DIN 40050-9: IP69K *4				
Weight (packed state/only sensor)	**Pre-wired cable (2M)**		**E3RA:** Approx. 110 g/ Approx. 50 g, respectively, **E3RB:** Approx. 175 g/ Approx. 65 g, respectively	**E3RA:** Approx. 60 g/ Approx. 50 g, **E3RB:** Approx. 95 g/ Approx. 65 g			
	Connector		**E3RA:** Approx. 30 g/ Approx. 10 g, respectively, **E3RB:** Approx. 85 g/ Approx. 20 g, respectively	**E3RA:** Approx. 20 g/ Approx. 10 g, **E3RB:** Approx. 50 g/ Approx. 20 g			
Material	**Case**		**E3RA:** ABS, **E3RB:** Nickel-brass				
	Lens and Display		PMMA				
	Adjuster		POM				
	Nut		**E3RA:** POM, **E3RB:** Nickel-brass				
Accessories			Instruction sheet M18 nuts (4 pcs)	Instruction sheet M18 nuts (2 pcs)			

Note: 1. Altitude: Up to 2,000 m, Pollution degree: 3, Enclosure type: Type1.
*1. UL power supply voltage rating is 10 to 26.4 VDC.
*2. UL load power supply voltage rating is 26.4 VDC max.
*3. UL temperature rating is 40°C maximum in operation.
*4. IP69K Degree of Protection Specifications
IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.
The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.
The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



Engineering Data (Reference Value)

Parallel Operating Range

Through-beam Models
E3F□-T□, E3R□-T□



Retro-reflective Models (with MSR function)
E3F□-R□1, E3R□-R□1



E3F□-R□2



Transparent detected with P-opaquing function
E3F□-B□1



E3F□-B□2



Operating Range

Diffuse-reflective Models
E3F□-D□1, E3F□-D□2
E3R□-D□1, E3R□-D□2



E3F□-D□3, E3R□-D□3



E3FA-D□4, E3FA-D□5



E3FA-D□6



BGS Models
E3F□-L□1, E3F□-L□2



Limited distance reflective
E3F□-V□



Excess Gain vs. Distance

Through-beam Models
E3F□-T□, E3R□-T□



Retro-reflective Models (with MSR function)
E3F□-R□1, E3R□-R□1



E3F□-R□2



Diffuse-reflective Models
E3F□-D□1, E3F□-D□2
E3R□-D□1, E3R□-D□2



E3F□-D□3, E3R□-D□3



E3FA-D□4, E3FA-D□5



E3FA-D□6



Transparent detected with P-opaquing function
E3F□-B□1, E3F□-B□2



Limited distance reflective
E3F□-V□



Sensing Object Size vs. Distance

Diffuse-reflective Models

E3F□-D□1, E3F□-D□2
E3R□-D□1, E3R□-D□2



E3F□-D□3, E3R□-D□3



E3FA-D□4, E3FA-D□5



E3FA-D□6



Sensing Distance vs. Sensing Object Material

BGS Models

E3F□-L□1



E3F□-L□2



Dark Excess Gain vs. Sensing Object Characteristics

Transparent detected with P-opaquing function

E3F□-B□1



E3F□-B□2



Object Surface Color vs. Sensing Distance

Diffuse-reflective Models

E3FA-D□1



E3FA-D□2



E3FA-D□3



E3FA-D□4



E3FA-D□5



E3FA-D□6



Output circuit diagram

PNP Output

Model	Operation mode	Timing charts	Operation selector	Output circuit
E3F□-TP□ E3F□-RP□ E3F□-DP□ E3F□-VP□ E3F□-BP□ E3R□-TP□ E3R□-RP□ E3R□-DP□	Light-ON		Connect the pink wire (Pin(2)) to the brown (Pin(1))	Through-beam Receivers, Retro-reflective Models, Diffuse-reflective Models, Limited reflective Models. Transparent detected with P-opaquing function. 
	Dark-ON		Connect the pink wire (Pin(2)) to the blue (Pin(3)) or open the pink wire (Pin(2))	
		Through-beam Emitter 		
E3F□-LP□	Light-ON		Connect the pink wire (Pin(2)) to the brown (Pin(1))	Background suppression. 
	Dark-ON		Connect the pink wire (Pin(2)) to the blue (Pin(3)) or open the pink wire (Pin(2))	

NPN Output

<table>
<tr><th>Model</th><th>Operation mode</th><th>Timing charts</th><th>Operation selector</th><th>Output circuit</th></tr>
<tr><td rowspan="3">E3F□-TN□
E3F□-RN□
E3F□-DN□
E3F□-VN□
E3F□-BN□
E3R□-TN□
E3R□-RN□
E3R□-DN□</td><td>Light-ON</td><td>
</td><td>Connect the pink wire (Pin(2)) to the brown (Pin(1)) or open the pink wire (Pin(2))</td><td rowspan="2">Through-beam Receivers, Retro-reflective Models, Diffuse-reflective Models, Limited reflective Models. Transparent detected with P-opaquing function.

</td></tr>
<tr><td>Dark-ON</td><td>
</td><td>Connect the pink wire (Pin(2)) to the blue (Pin(3))</td></tr>
<tr><td colspan="4">Through-beam Emitter

</td></tr>
<tr><td>E3F□-LN□</td><td>Light-ON</td><td>
</td><td>Connect the pink wire (Pin(2)) to the brown (Pin(1)) or open the pink wire (Pin(2))</td><td>Background suppression.

</td></tr>
<tr><td>Dark-ON</td><td>
</td><td>Connect the pink wire (Pin(2)) to the blue (Pin(3))</td></tr>
</table>

Connector Pin Arrangement

M12 Connector Pin Arrangement



Connectors (Sensor I/O connectors)

M12 4-wire Connectors



Classification	Wire color	Connector pin No.	Application
DC	Brown	(1)	Power supply (+V)
	White	(2)	L/on · D/on selectable
	Blue	(3)	Power supply (0 V)
	Black	(4)	Output

Nomenclature

Straight type, Plastic housing

with an adjuster:
E3FA-T□-D
E3FA-R□
E3FA-D□
E3FA-V□
E3FA-B□
without an adjuster:
E3FA-T□-L *
E3FA-L□



Radial type, Plastic housing

with an adjuster:
E3RA-T□-D
E3RA-R□
E3RA-D□
without an adjuster:
E3RA-T□-L *



* The Emitter has two Power indicators (Green) instead of the Stability indicator (Green) and the Operation indicator (Orange).

Straight type, Metal housing

with an adjuster:
E3FB-T□-D
E3FB-R□
E3FB-D□
E3FB-V□
E3FB-B□
without an adjuster:
E3FB-T□-L *
E3FB-L□



Radial type, Metal housing

with an adjuster:
E3RB-T□-D
E3RB-R□
E3RB-D□
without an adjuster:
E3RB-T□-L *



* The Emitter has two Power indicators (Green) instead of the Stability indicator (Green) and the Operation indicator (Orange).

Safety Precautions

Refer to *Warranty and Limitations of Liability*.

⚠ WARNING

This product is not designed or rated for directly or indirectly ensuring safety of persons. Do not use it for such a purpose.



⚠ CAUTION

Never use the product with an AC power supply.
Do not use the product with voltage in excess of the rated voltage.



Do not use the product with incorrect wiring.
Otherwise, explosion, fire, malfunction may result.



Precautions for Safe Use

Be sure to follow the safety precautions below for added safety.

1. Do not use the sensor under the environment with explosive, flammable or corrosive gas.
2. Do not use the sensor under the oil or chemical environment.
3. Do not use the sensor in the water, rain or outdoors.
4. Do not use the sensor in the environment where humidity is high and condensation may occur.
5. Do not use the sensor under the environment under the other conditions in excess of rated.
6. Do not use the sensor in place that is exposed by direct sunlight.
7. Do not use the sensor in place where the sensor may receive direct vibration or shock.
8. Do not use the thinner, alcohol, or other organic solvents.
9. Never disassemble, repair nor tamper with the sensor.
10. Please process it as industrial waste.

Precautions for Correct Use

1. Laying Sensor wiring in the same conduit or duct as high-voltage wires or power lines may result in malfunction or damage due to conduit or use shielded cable.
2. Do not pull on the cable with excessive force.
3. If a commercial switching regulator is used, ground the FG (frame ground) terminal.
4. The sensor will be available 100 ms after the power supply is tuned ON. Start to use the sensor 100 ms or more after turning ON the power supply. If the load and the sensor are connected to separate power supplies, be sure to turn ON the sensor first.
5. Output pulses may be generated even when the power supply is OFF. Therefore, it is recommended to first turn OFF the power supply for the load or the load line.
6. The sensor must be mounted using the provided nuts. The proper tightening torque range of E3FA/E3RA plastic housing series is between 0.4 and 0.5 N·m. The proper tightening torque of E3FB/E3RB metal housing series is 20 N·m max..

Dimensions

(Unit: mm)
Tolerance class IT16 applies to dimensions in this data sheet unless otherwise specified.

Sensors (E3FA/E3RA Plastic housing)

E3FA series
Pre-wired Models
E3FA-T□1□
E3FA-R□1□
E3FA-D□1□
E3FA-L□1□
E3FA-V□11
E3FA-B□1□



Front view



Left side view



Suitable models
E3FA-T□1□
E3FA-R□12
E3FA-B□11

Left side view



Suitable models
E3FA-R□11
E3FA-D□1□
E3FA-L□1□
E3FA-V□11
E3FA-B□12

*** Suitable models**
E3FA-T□1□-D
E3FA-R□12
E3FA-D□1□
E3FA-V□11
E3FA-B□12

Mounting Holes



E3FA series
M12 Connector Models
E3FA-T□2□
E3FA-R□2□
E3FA-D□2□
E3FA-L□2□
E3FA-V□21
E3FA-B□2□



Front view



Right side view



Left side view



Suitable models
E3FA-T□2□
E3FA-R□22
E3FA-B□21

Left side view



Suitable models
E3FA-R□21
E3FA-D□2□
E3FA-L□2□
E3FA-V□21
E3FA-B□22

*** Suitable models**
E3FA-T□2□-D
E3FA-R□22
E3FA-D□2□
E3FA-V□21
E3FA-B□22

Mounting Holes



Terminal No.	Specification
1	+V
2	L/on · D/on selectable
3	0V
4	Output

E3RA series
Pre-wired Models
E3RA-T□11
E3RA-R□11
E3RA-D□1□



Rear view



Suitable models
E3RA-T□11

Rear view



Suitable models
E3RA-R□11
E3RA-D□1□

Front view



Mounting Holes



E3RA series
M12 Connector Models
E3RA-T□21
E3RA-R□21
E3RA-D□2□



Rear view



Suitable models
E3RA-T□21

Rear view



Suitable models
E3RA-R□21
E3RA-D□2□

Front view



Bottom view



Mounting Holes



Terminal No.	Specification
1	+V
2	L/on · D/on selectable
3	0V
4	Output

Sensors (E3FB/E3RB Metal housing)

E3FB series
Pre-wired Models
E3FB-T□11
E3FB-R□1□
E3FB-D□1□
E3FB-L□1□
E3FB-V□11
E3FB-B□1□



Left side view



Suitable models
E3FB-T□11
E3FB-R□12
E3FB-B□11

Left side view



Suitable models
E3FB-R□11
E3FB-D□1□
E3FB-L□1□
E3FB-V□11
E3FB-B□12

Front view



*** Suitable models**
E3FB-T□11-D
E3FB-R□12
E3FB-D□1□
E3FB-V□11
E3FB-B□12

Mounting Holes



E3FB series
M12 Connector Models
E3FB-T□21
E3FB-R□2□
E3FB-D□2□
E3FB-L□2□
E3FB-V□21
E3FB-B□2□



Left side view



Suitable models
E3FB-T□21
E3FB-R□22
E3FB-B□21

Left side view



Suitable models
E3FB-R□21
E3FB-D□2□
E3FB-L□2□
E3FB-V□21
E3FB-B□22

Front view **Right side view**



*** Suitable models**
E3FB-T□21-D
E3FB-R□22
E3FB-D□2□
E3FB-V□21
E3FB-B□22

Mounting Holes



Terminal No.	Specification
1	+V
2	L/on · D/on selectable
3	0V
4	Output

E3RB series
Pre-wired Models
E3RB-T□11
E3RB-R□11
E3RB-D□1□



Rear view



Suitable models
E3RB-T□11

Rear view



Suitable models
E3RB-R□11
E3RB-D□1□

Front view



Mounting Holes



E3RB series
M12 Connector Models
E3RB-T□21
E3RB-R□21
E3RB-D□2□



Rear view



Suitable models
E3RB-T□21

Rear view



Suitable models
E3RB-R□21
E3RB-D□2□

Front view



Bottom view



Mounting Holes



Terminal No.	Specification
1	+V
2	L/on · D/on selectable
3	0V
4	Output

Attached nut



Material:POM(for E3FA/E3RA)
Nickel-brass(for E3FB/E3RB)

Accessories (Order Separately)

Reflectors

E39-R1S



E39-RP1



Material,
reflective surface: acrylic
Rear surface: ABS

Mounting brackets

E39-L183



Mounting brackets

E39-L182



ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

Note: Do not use this document to operate the Unit.

OMRON Corporation **Industrial Automation Company**

Kyoto, JAPAN **Contact : www.ia.omron.com**

Regional Headquarters

OMRON EUROPE B.V.
Wegalaan 67-69, 2132 JD Hoofddorp
The Netherlands
Tel: (31) 2356-81-300 Fax: (31) 2356-81-388

OMRON ELECTRONICS LLC
2895 Greenspoint Parkway, Suite 200
Hoffman Estates, IL 60169 U.S.A.
Tel: (1) 847-843-7900 Fax: (1) 847-843-7787

OMRON ASIA PACIFIC PTE. LTD.
438B Alexandra Road, #08-01/02 Alexandra
Technopark, Singapore 119968
Tel: (65) 6835-3011 Fax: (65) 6835-3011

OMRON (CHINA) CO., LTD.
Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
PuDong New Area, Shanghai, 200120, China
Tel: (86) 21-6023-0333 Fax: (86) 21-5037-2388

Authorized Distributor:

©OMRON Corporation 2012-2025 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

CSM_4_4
Cat. No. E423-E1-06 1225 (0612)