Anybus X-gateway - CANopen Slave - POWERLINK Device

Item number: AB7531-F

The Anybus X-gateway CANopen Slave to POWERLINK Device enables you to connect any Modbus RTU system to any POWERLINK control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects CANopen and POWERLINK control systems

Features and benefits

Reach new markets

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.

Slim hardware design

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

Easy configuration – No programming required!

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.

Trusted partner

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

No PLC card slot needed

The gateway does not use a card slot in the control system, leaving room for other equipment.

1-year warranty

The gateway is designed to be robust and long-lasting. A 1-year guarantee is provided

Increased PLC performance

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.

Life cycle management

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway - CANopen Slave - POWERLINK Device



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus X-gateway - CANopen Slave - POWERLINK Device



General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AB7531-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x D-sub 9-pin male, USB-B Config port
DIP & Rotary Switches	3x Rotary CAN Address + Baudrate
Contains Battery	No

CANopen Features

CANopen Mode	Slave mode
CANopen Baud Rate	10 kbit/s - 1000 kbit/s
CANopen Supported Functionality	PDO, SDO;DS301 v4.02
CANopen Configuration File	EDS available
CANopen Input Data Size	512 bytes
CANopen Output Data Size	512 bytes

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE

Anybus X-gateway - CANopen Slave - POWERLINK Device



Certifications and Standards

Product Certifications	CE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment