Ixxat CAN-IB300/PCI

Item number: 1.01.0291.12001

The Ixxat CAN-IB300/PCI is a passive PCI interface card with one CAN channel and galvanic isolation. It is an easy and cost-efficient way to connect computers to a CAN bus network. Based on a modular design, the card enables simple integration into diverse industrial setups, supporting various CAN applications.



PC interface card for CAN (1 x CAN), galv. isolated

Features and benefits

Passive CAN interface card

Direct access to CAN networks – suitable for applications where a straightforward, microcontroller-free connection is required.

PCI interface

PCI (V2.2) plug&play interface supports high-speed data transmission, ideal for demanding industrial applications.

Standard slot bracket

Standard slot bracket size ensures compatibility with a wide range of PC systems.

Modular architecture for easy expansion

Modern and modular concept enables easy extension with customer specific interfaces via expansion boards and piggyback modules.

Overvoltage protection

Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.

Powerful programming interface

Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.

Cost-effective connectivity

Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.

Use in industrial and standard PCs

PC board with slot plate for fixed installation in desktop or industrial PCs, providing reliable connectivity.

Installation of multiple cards

Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.

Expandable low-speed CAN channel

Expansion boards for additional low-speed CAN channel supported – switchable through software.

Comprehensive driver compatibility

Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.

Analysis software included

Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.

Ixxat CAN-IB300/PCI



General

Net Width (mm)	64
Net Height (mm)	120
Net Weight (g)	190
Packed Width (mm)	13
Packed Height (mm)	5
Packed Depth (mm)	18
Packed Weight (g)	205
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	100 mA (3.3 VDC), 100 mA (5 V DC)
Input Voltage (V)	3.3/5 V DC via PCI socket
Isolation	1 kV DC for 1 sec.
Content of Delivery	PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download
Mounting	PCI
Packaging Material	Cardboard
Warranty (years)	1

Ixxat CAN-IB300/PCI



Identification and Status

Product ID	1.01.0291.12001
Country of Origin	Germany
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1 x D-Sub 9 connector, 1 x PCI (V2.2)
Contains Battery	No

CAN Features

CAN Mode	CAN high-speed (ISO 11898-2), via optional expansion: CAN low-speed (ISO 11898-3)
CAN Transceiver	TLE6250GV33
CAN Controller	CAN 2.0 A/B
CAN Baud Rate	CAN high-speed: 10 kBit/s to 1 Mbit/s, via optional expansion: CAN low-speed: 10 kBit/s to 125 kBit/s

Certifications and Standards

Product Certifications	CE, FCC
WEEE Category	IT and telecommunications equipment