LİTHĪUMVALLEY



Residential LFP Battery Series

LV-BAT-W10.24Ac

51.2V 200Ah 10.24kWh

A sleek and space-saving solution for your energy storage needs. With its compact design and easy installation, it seamlessly blends into any environment. Whether in your home, office, or commercial space, our wall-mounted unit provides reliable and efficient energy storage.







LV-BAT-W10.24Ac is a perfect wall-mounted solar energy lithium battery for residential home use. Built-in with High-Quality LiFePO4 large capacity cells. It ensures a long cycle life of the battery system. The designed BMS is verified to be compatible with different brands of inverters, hybrid on grid&off grid or off grid.

DONGUAN LITHIUM VALLEY ENERGY CO., LTD .

FEATURES



Unique Design New wall mount design







Flexible Capacity Max.15pcs in Parallel to extend capacity

Easy Installation

Quick plug in +/- and

parallel connection



Safe & Reliable Lithium Iron Phosphate (LFP) Cell

•

Certificates CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619 ; UN38.3, MSDS

Dimensions







	-	•	••	•	

Model	LV-BAT-W10.24Ac
Nominal Voltage	51.2V
Rated Capacity	200Ah
Energy	10240Wh
Charging Cut-off Voltage	56.16V
Discharge Cut-off Voltage	45.6V
Recommend charge/discharge current	100A
Maximum continuous charge/discharge current	200A
Instantaneous discharge current	400A/3S
Charge temperature	0~55°C
Discharge temperature	−20~60°C
Storage Environment (50% state of charge)	20°C ~ 45°C in three months; 25±3°C over three months; Humidity:65±20%RH
Environment	Indoor/outdoor under roof (avoid direct sunlight)
Installation	Wall mounted
Cell Technology	Lithium iron phosphate (LiFePO4)
Life Cycle	6000 times @80%DOD
Cooling	Natural convection
Protection Rating	IP65
Certificates	CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619 ; UN38.3, MSDS

Dimension and Weight

Dimension

Battery Net Weight/Gross Weight

Communication Instruction

Communication

*The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment. *The specifications are subject to change without prior notice.



Factory Address: No. 11, Yinyang Road, Zhangyang Community, Zhangmutou Town, Dongguan

800*590*142mm

98KG/106KG

RS232, CAN, RS485

