

Product Overview

- HEPA grade air filtration media with superior strength and antimicrobial properties
- The filter media performance was tested against bacteria and virus
- Lowest possible pressure drop without compromising antimicrobial properties
- Made of fibreglass media immobilized with antimicrobial agents to combat harmful microorganisms
- New innovation media not only traps small particles, but also minimizes the number of microbes by inhibiting their growth and reproduction



Specification

EN1822	H13	
JIS Z 2801*	100%**	
ISO 18184*	99.9%**	
Filter Depth (mm)	292	
Media Type	Fibreglass with antimicrobial properties	
Frame Material (Standard)	Galvanised Steel	
Frame Material (Optional)	Stainless Steel, Aluminium	
Separator Style	Hot Melt	
Gasket Material (Standard)	PU	
Gasket Material (Optional)	Neoprene, EPDM	
Gasket Position (Standard)	Downstream	
Gasket Position (Optional)	Upstream, Both Sides	
Special Size Available	No	
Antimicrobial Available	Yes	
Header Type	None Header	
Recommended Final Resistance	750 Pa	
Max Operating Temperature	70°C	

Product Information

Part Number	Actual Size mm (H x W x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
H13 S+			
MA570-206-004	610 x 305 x 292	1,750	250
MA570-206-005	610 x 610 x 292	3,500	

*The test on filter media was done in a controlled environment. Actual performance may differ in different conditions and environments.

**The efficacy shown applies only to the tested specimens: COVID-19 (SARS-CoV-2), Influenza A virus (H1N1), Human Coronavirus 229E, Staphylococcus aureus, and Escherichia coli. All tests were conducted on media that had been exposed to specific viruses and bacteria within a specific regulated time period of 24 hours of contact time, aside from SARS-CoV-2, which had 30 minutes of contact time. Performance against other viruses and bacteria may vary.