



Product Overview

- Individually tested for certified performance
- Hot-melt separator-style glass media pack
- No metal in airstream
- Gasket seal



Specification

EN1822	H13, H14
Filter Depth (mm)	149, 292
Media Type	Fibreglass
Frame Material (Standard)	Galvanised Steel
Frame Material (Optional)	Aluminium, Stainless Steel Plywood, Particle Board
Separator Style	Hot Melt
Gasket Material (Standard)	Neoprene
Gasket Material (Optional)	PU, EPDM
Gasket Position (Standard)	Downstream
Gasket Position (Optional)	Upstream, Both Sides
Faceguard	No
Special Size Available	Yes
Antimicrobial Available	No
Header Type	None Header
Recommended Final Resistance	500 Pa
Max Operating Temperature	70°C

Product Information

Part Number	Actual Size mm (H x W x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
H13			
M746-203-004	610 x 305 x 149	650	250
M746-203-005	610 x 610 x 149	1,300	
M646-203-004	610 x 305 x 149	1,000	
M646-203-005	610 x 610 x 149	2,000	
M846-205-004	610 x 305 x 292	1,150	
M846-205-005	610 x 610 x 292	2,300	
H14			
M743-203-004	610 x 305 x 149	475	250
M743-203-005	610 x 610 x 149	950	
M643-203-004	610 x 305 x 149	750	
M643-203-005	610 x 610 x 149	1,500	
M843-205-004	610 x 305 x 292	875	
M843-205-005	610 x 610 x 292	1,750	