



BioCel VXL

Product Overview

- Engineered to meet the exacting requirements of precision manufacturing operations and laboratories
- Fills the gap between ASHRAE grade high-efficiency filters and high efficiency HEPA filters
- Low initial pressure drop
- High impact polystyrene (HIPS) cell sides
- Fully incinerable

Specification

EN1822	E10, E11
Filter Depth (mm)	304
Media Type	Fibreglass
Frame Material	Plastic
Separator Style	Hot Melt
Special Size Available	No
Antimicrobial Available	No
Header Type	Single Header
Gasket Material (Standard)	Neoprene
Gasket Material (Optional)	PU, None
Recommended Final Resistance	500 Pa
Max Operating Temperature	70°C



Product Information

Part Number	Nominal Size Inches (W x H x D)	Actual Size mm (W x H x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
E10				
M336-124-003N	24 x 12 x 12	592 x 287 x 304	1,700	150
M336-124-002N	24 x 20 x 12	592 x 490 x 304	2,800	
M336-124-001N	24 x 24 x 12	592 x 592 x 304	3,400	
E11				
M336-128-003N	24 x 12 x 12	592 x 287 x 304	1,700	180
M336-128-002N	24 x 20 x 12	592 x 490 x 304	2,800	
M336-128-001N	24 x 24 x 12	592 x 592 x 304	3,400	