



Product Overview

- Minipleat with ribbon separator
- Panel filter with aluminium extrusion frame
- Silicone free construction
- 385°C maximum temperature

Specification

EN779	M6 - F8
ASHARE 52.2	MERV 11 - 14
Filter Depth (mm)	55, 78
Media Type	Fibreglass
Frame Material	Aluminium
Separator Style	HT Proseal Tech
Gasket Material	Glass Rope
Special Size Available	Yes
Antimicrobial Available	No
Header Type	None Header
Recommended Final Resistance	≤ 500 Pa
Max Operating Temperature	385°C
Air Filtration Certificate	UL 900



Product Information

Nominal Size Inches (H x W x D)	Actual Size mm (H x W x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
M6 / MERV 11			
12 x 24 x 2	305 x 610 x 55	300	80
24 x 24 x 2	610 x 610 x 55	600	
12 x 24 x 3	305 x 610 x 78	300	75
24 x 24 x 3	610 x 610 x 78	600	
F7 / MERV 13			
12 x 24 x 2	305 x 610 x 55	300	80
24 x 24 x 2	610 x 610 x 55	600	
12 x 24 x 3	305 x 610 x 78	300	75
24 x 24 x 3	610 x 610 x 78	600	
F8 / MERV 14			
12 x 24 x 2	305 x 610 x 55	300	80
24 x 24 x 2	610 x 610 x 55	600	
12 x 24 x 3	305 x 610 x 78	300	75
24 x 24 x 3	610 x 610 x 78	600	