HDMI CABLE High Speed With Ethernet PCT-HD-xA-y



Innovation for the Last Mile[®]



Superior Audio / Video Signal Performance

PCT's enhanced shielding performance High Definition Multimedia Interface (HDMI[®]) cables by PCT[®] provide high speed, modern home theater connections. With just one cable, uncompressed audio and video signals are transmitted between consumer electronic devices. This cable provides crisp, clear sound and a sharp, clear picture with bright, lifelike colors and accurately detailed images.

Offering our customers products and services with the highest quality performance and long-term reliability is always at the peak of our objectives. That's why PCT's factory has earned the official Certified HDMI Adopter status with HDMI Licensing, LLC. For our customers, this means when you purchase PCT's High Speed HDMI cables, you know that our cables are designed and tested in accordance with stringent HDMI Adopter Agreement specifications. PCT's High Speed HDMI cable truly delivers excellent sight and sound with lasting quality and performance.

PCT HDMI cable packaging includes retail and non-retail options and offers customer customization of material, size, shape and artwork. PCT's quality packaging solutions focus on customer specifications and objectives, ease of handling, shipping optimization and sustainability.

Recommended use for the following applications:

- HD and 4K resolution equipment including:
 - Set tops
 - Televisions
 - DVR equipment
 - Video gaming systems
 - Blu-ray and DVD players
- ✓ Computers and laptops
- Devices with HDMI compliant ports



Homi

RoHS

(VL)

HDMI, the HDMI logo and High Definition Multimedia Interface are trademarks or registered trademarks or HDMI Licensing LLC in the United States and other countries. UL and the UL logo are trademarks of UL LLC.





Call +1.800.306.8948 or email pctcustomerservice@pctintl.com for more information 2260 W Broadway Rd | Mesa AZ 85202-1898 | USA | pctinternational.com © 2014-2017 PCT International, Inc. Innovation for the Last Mile and PCT are egistered trademarks of PCT International, Inc.



			PCT-HD-xA-y		
	fications		3	6	10
Parameter		Unit		Details	
ELECTRI	CAL SPECIFICATIONS	5			
Voltage		V	30		
RFI Shielding 5 to 1002 MHz		dB	30		
Impedance		Ohm	$100 \pm 10\%$		
Spark Test (min)		VAC / sec	500 / 0.15		
Dielectric Strength (min)		VAC / sec	750 / 1		
Insulation Resistance (min)		VDC mOhm / 1000 ft (mOhm / Km)	500 30.5 @ 68° F (100 @ 20° C)		
Conductor Resistance (min)		Ohm / 1000 ft @ 68° F (Ohm / Km @ 20° C)	114.6 64.6 (376) (212)		
PHYSICA	AL CHARACTERISTIC	S			
Connector Color and Molding			Black w/ PCT logo		
Cable Type			Category 2		
Length		ft (m)	3 (0.95)	6 (1.83)	10 (3.05)
Braid Coverage (min)			90 %		
Jacket			PVC (black)		
Diameter Over Jacket (nom)		in (mm)	0.24	(6.1)	0.28 (7.1)
Connector	Hold Retention (typical)	lbf (N)	5.5 (24.5)		
	Interface		19-pin HDMI Type A		
	Plating		Nickel		
Conductor Size		AWG	30		28
Temperature Rating		°F (°C)	176 (80)		
COMPLI	ANCE & CERTIFICATI	ONS			
Compliance			HDMI, UL Type 20276 VW-1 & RoHS		
Certifications			HDMI Adopter, ATC 1.4		



Ordering Information

PCT-HD-xA-y

HDMI Cable, High Speed with Ethernet, Enhanced Shielding

x = length in feet:3, 6 or 10
Custom lengths available.y = packaging type:P1 (heat sealed bag), P2 (box), P3 (clamshell),
P4 (blister pack), P5 (molded fiber),
P6 (point of purchase display)
Leave blank for bulk packaging.
Additional packaging types and customization available.





© 2014-2017 PCT International, Inc. Innovation for the Last Mile and PCT are stered trademarks of PCT International, Inc.